

Multi-track technology for the 21st century

BLACKBOX RECORDER

Unique technology lets you capture live multi-channel audio without taking a computer or DAW to the performance



24 TRACK • 24 BIT • 96kHz

The JoeCo **BLACKBOX RECORDER** is the first large-scale multi-channel recorder specifically designed for audio acquisition and capturing live performance. Developed to solve the inherent problems of working with computer-based systems in a live environment, it provides engineers with a computer-free, high-quality solution for live multi-channel audio capture.

Able to record or replay up to 24 channels of 24bit/96kHz audio, the **BlackBox Recorder** is available in both analogue and digital variants, offering a choice of professional interfaces to any live mixing console. Units can be linked for recordings involving larger track counts.

Audio is recorded as mono broadcast WAV files to an external USB2 drive, or USB2 Flash drive. Using universally accepted file and disk formats on external storage solutions has many advantages when used in the field or on tour. It also eliminates the time normally required to load recordings into a workstation for subsequent mixing and re-purposing, which is a crucial factor in fast turnaround productions. Recorded files can be instantly imported into any Mac- or PC-based Digital Audio Workstation for editing, remixing and re-purposing.

The **BlackBox Recorder** is designed to be supremely simple to use, requiring just the input and output connections, power and a USB drive before pressing the RECORD button. A full colour LCD screen and striking LED displays show all the information that's needed in order to know exactly what's happening. A standard computer keyboard can be used to name recordings. The recorder is also equipped with a range of fail-safe features to keep recordings as secure as possible, including the ability to recover files should power fail during a recording.

Since its release in 2009, the **BlackBox Recorder** has won a series of international awards from industry press, readers and trade associations, including a PLASA Award for Innovation and a TEC Award for Best Recording Device. The recorder has a wide range of applications in Live Performance, Broadcast, Film & TV Sound and Post Production.



- 24-channel record or playback @ up to 24bit/96kHz.
- Multiple units can be linked together for large recordings.
- Only 1 rack unit tall (435 x 44 x 170mm) and weighing just 2.1kg.
- Unbalanced or Balanced analogue, AES/EBU and Lightpipe digital i/o options. (64-channel MAD1 and Dante versions also available - see separate flyers.)
- Records standard broadcast WAV files to an external USB2 drive, or USB Flash drive.
- Captured audio material can be used in any digital audio workstation for instant re-purposing without time consuming file transfers.
- Simple to operate and understand.
- Attaches to any live console to provide virtual sound checking.
- Fail-safe features for secure audio capture.
- Track, song and folder naming.
- * Allows the creation of headphone monitor mixes with level and pan on each track.
- Remote control via QWERTY keyboard, MIDI, Sony 9-pin.

BBR1U

Unbalanced i/o via 3 x 25way D-sub connectors (3 x 1/4" TRS multicore looms supplied - TASCAM analogue format). Designed to plug across the insert points on a standard analogue console.

BBR1B

Balanced i/o via 6 x 25way D-sub connectors. Lower row - inputs; Upper row - outputs. (TASCAM analogue format, cable looms not supplied.)

BBR1A

Lightpipe i/o via 3 x TOSLINK inputs and 3 x TOSLINK outputs (24 channels @ 48k, 12 channels @ 96k). Word clock input on BNC. Unbalanced analogue as BBR1-U (cable looms not supplied).

BBR1D

AES3 (2003) i/o via 3 x 25way D-sub connectors - upper row. (Yamaha format pin out standard.) Word clock input on BNC. Unbalanced analogue as BBR1-U (cable looms not supplied).

BLACKBOX RECORDER Distributed by:

Technical Specifications:

General

Sample rates: 44.1kHz, 48kHz, 88.2kHz, 96kHz

Bit depths: 16 / 24bit

Disk interface: USB2 - easy to obtain

Disk format: FAT32 - compatible with both Mac and PC

File type: Standard mono Broadcast WAV files

Monitoring: 1 x 1/4" TRS jack socket, headphone mix / solo

Physical: 19" rack mounted 1U (435x44x170mm). Weight 2.1kg

Power: 9V-16V dc (<30W). 2.1mm dc inlet. PSU supplied

Audio i/o: Analogue inputs / outputs

Levels: -10dBu / +4dBu switchable

Max input / output level: +22dBu = 0dBFS

A-D / D-A conversion: 24bit, 96kHz 106dB S/N, 96dB THD+N (typical A-weighted)

Control and Synchronisation

MIDI: 1 x 5-pin DIN (open loop). MIDI time code (MMC) and MIDI Machine Control (MMC) protocol

LTC: 1 x 1/4" TRS jack socket. Frame rates supported: 30fps, 29.97 drop fps, 25fps, 24fps, 23.98fps

Machine control: 1 x 9-pin D, SONY PII protocol

Audio clock synchronisation: 2 x RCA sockets AES3 / SPDIF format, also used for communications to slave units



Loop through outputs available on ch 17-24 on 1/4" TRS jack sockets for connection to outboard equipment



No loop through outputs. Other connectors as BBR1-U



Loop through outputs as BBR1-U available on analogue i/o only. Other connectors as BBR1-U



Loop through outputs as BBR1U available on analogue i/o only. Other connectors as BBR1U

JoeCo Limited. Registered in England: 6361413 VAT Number: GB 923 8706 10. All rights reserved. Any trademarks and intellectual property rights are acknowledged as the property of their respective owners. JoeCo Limited reserves the right to make changes to specifications at any time and without prior notice. E&OE etc.

**JoeCo Limited. 135 Histon Road,
Cottenham, Cambridge, CB24 8UQ, U.K.
info@joeco.co.uk**