

Hi-Definition USB Audio Adapter.



new versions

PUC2

Plug'n'Play USB 2.0 Audio Adapter for both analog balanced line and digital audio (AES3)

Hi-Def AD/DA converters with 24 Bit and sample rates from 44,1-192 KHz



Balanced analog audio level up to +18dB (full scale) on XLR with selectable operating levels: +4dBu, +6dBu or user definable

Common to all versions:

Sleek and robust aluminium case with rubber linings. Future proof modular design

Unique ZLM (Zero Latency Monitoring)

PUC2 Lite

Value USB 2.0 Audio Adapter for digital audio only (AES3)

Plug'n'Play supports native drivers of Microsoft XP/Vista/WIN7 and MAC OS9 or higher



GPI for ZLM remote switching

Powered over USB - keeps the power brick and the hassle away

ASIO, WDM drivers (XP/Vista/WIN7) for 32 and 64 Bit and HAL plugin (MAC OS9+) available without charge for extended functions

PUC2 Mic

USB 2.0 Audio Adapter for MIC, analog balanced line and digital audio (AES3) with 1/4" H/P output

Drivers and software for MIC pre amplifier settings included



Fantastic -128dBu input referred noise figure

Switchable phantom power 48V

Hi Pass Filter (selectable)

Phase reverse and more

Extended ZLM features for smarter monitor mix

www.yellowtec.com

Designed and Made in Germany