BlueDriver-M3[™] [⊗]

Wireless Audio Interface

Headset Connect BlueDriver-M3TM Phone JK AudioTM Power Send

7 kHz

HD VOICE

FEATURES	D3	F3	М3
» HD Voice (Wide-Band Speech)	•	•	•
» 3-pin Female XLR Input	•	•	
» 3-pin Male XLR Output	•		•
» 3.5 mm Input	•		•
» 3.5 mm Output	•	٠	
» 3.5mm Earpiece/Headphone Output		•	
» Trim Pot Adjusts Mic Level		٠	
» Headset/Phone Switch		•	•
» Mini USB Power Jack		٠	•
 » > 18 Hours on one 9-volt Alkaline Battery 	•		
» >6 hours on Internal Li-Ion Battery		•	•

BlueDriver-F3 and Daptor Three shown for comparison.

D3 =Daptor Three F3 = BlueDriver-F3 M3 = BlueDriver-M3

Bluetooth Device to Mic Input.

Pair to your Bluetooth equipped cell phone or headset to get audio straight from your Bluetooth device into your Mic input. The 3.5 mm send jack will accept a signal from the headphone output of the mixer for transmission back to the cell phone or headset.

Headset Mode vs. Phone Mode

A switch selects between connection to a Bluetooth headset or speaker, or to a phone.

Headset Connect:

Pair BlueDriver-M3 to your 3rd party Bluetooth headset. Some Bluetooth headsets allow you to switch between your audio device and a cell phone.

Phone Connect:

Pair BlueDriver-M3 to your cell phone to call into the station or bring in caller audio.



© 2018, JK Audio, Inc. 1311 E. 6th St. Sandwich, IL. 60548 800.552.8346 • 815.786.2929 Se Habla Español

jkaudio.com info@jkaudio.com





Wireless Audio Interface

7 kHz DVOICE

Wireless Applications



Take Calls During a Live Remote Broadcast

This setup allows voice band, bi-directional audio to and from your cell phone.



Receive A2DP Audio from a Bluetooth Device

Stream full-bandwidth A2DP audio from your Bluetooth device.



Send A2DP Audio to your Bluetooth Device

Stream full-bandwidth A2DP audio to your Bluetooth device.



Bluetooth Headset as a Talkback Intercom

This setup allows voice-band bi-directional audio up to 66 ft from the BlueDriver-M3.

SPECIFICATIONS

Input	
1/8" (3.5mm) Stereo:	20k ohms / -10 dBu nom.
Output	
3-pin Male XLR:	1k ohms / -34 dBu nom.
Misc.	
Battery:	250 mAh Internal Lithium-Ion Polymer Rechargeable Battery with a Mini-USB Charging Port
Size:	1.1" x 4.4" (2.8 cm x 11.2 cm)
Weight:	2.1 oz. (60 g)

Bluetooth Wireless Technology

Standard:	Bluetooth 3.0	
Frequency Response:	Hands-Free (Full Duplex): 300 Hz– 3.4 kHz Hands-Free (Full Duplex HD): 50 Hz– 7 kHz A2DP (Master » Headset): 30 Hz–17 kHz	
End-to-End Latency:	Audio Recording: 25 ms using HD Voice Profile. Streaming Full Bandwidth Audio: 150 ms using Bluetooth A2DP Profile.	
Range:	66 ft (20 m)	

The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by JK Audio, Inc. is under license.

© 2018, JK Audio, Inc. 1311 E. 6th St. Sandwich, IL. 60548

800.552.8346 • 815.786.2929 Se Habla Español

jkaudio.com info@jkaudio.com



CE