

HD 3216T

PLASTIC HORN SPEAKER WITH DRIVER AND TRANSFORMER

DESCRIPTION

The HD 3216/T are compact, lightweight and watertight horn speakers. They are designed to provide high efficiency and characterized by the high intelligibility of the reproduced sound with low distortion. The built-in line transformer makes it possible to connect the horn loudspeaker to both 70 and 100 V constant voltage lines, and select the delievered power by means of a rotary dial on the rear cover



FEATURES

- Built-in line transformer with multitap power selector on rear cover
- Hi-pass filter for protecting driver against out-of-range low-freq
- IP 66 construction for indoor-outdoor environmental temperature between -25°C to +70°C
- UV-stabilized autoextinguishing UL-HB ABS plastic
- Colour RAL 7035
- Stainless-Steel mounting hardware



TECHNICAL SPECIFICATIONS

Max SPL @ 1m: 122 dB Horizontal coverage angle: 130° Vertical coverage angle: 60° System Sensitivity: 108 dB Power section Nominal Impedance (ohm): 8 ohm Power Handling: 25 W RM Peak Power Handling: 100 W P Recommended Amplifier: 50 W Transducers Compression Driver: 1.5"	
Vertical coverage angle: 60° System Sensitivity: 108 dB Power section Nominal Impedance (ohm): 8 ohm Power Handling: 25 W RN Peak Power Handling: 100 W P Recommended Amplifier: 50 W Transducers Compression Driver: 1.5"	
Vertical coverage angle: 60° System Sensitivity: 108 dB Power section Nominal Impedance (ohm): 8 ohm Power Handling: 25 W RN Peak Power Handling: 100 W P Recommended Amplifier: 50 W Transducers Compression Driver: 1.5"	
Power section Nominal Impedance (ohm): 8 ohm Power Handling: 25 W RM Peak Power Handling: 100 W P Recommended Amplifier: 50 W Transducers Compression Driver: 1.5"	
Power Handling: 25 W RM Peak Power Handling: 100 W P Recommended Amplifier: 50 W Transducers Compression Driver: 1.5"	
Peak Power Handling: 100 W P Recommended Amplifier: 50 W Transducers Compression Driver: 1.5"	
Recommended Amplifier: 50 W Transducers Compression Driver: 1.5"	EAK
Transducers Compression Driver: 1.5"	
Input/Output section Input connectors: Cable	
Output connectors: Cable	
Constant Voltage Transformer: 70/100 V	V
Power selection 1 (100 V): 25 W - 4	+00 ohm
Power selection 2 (100 V): 20 W - 5	500 ohm
Power selection 3 (100 V): 15 W - 66	67 ohm
Power selection 4 (100 V): 10 W - 10)00 ohm
Power selection 5 (100 V): 5 W - 20)00 ohm
Power selection 6 (100 V): 2.5 W - 4	4000 ohm
Standard compliance IP protection grade: IP 66	
CE marking: Yes	
Physical specifications Cabinet/Case Material: ABS	
Hardware: Stainless	s steel U bracket
Color: Grey - R.	AL 7035
Size Height: 170 mm	/ 6.69 inches
Width: 315 mm,	/ 12.4 inches
Depth: 322 mm	/ 12.68 inches
Weight: 1.87 kg /	4.12 lbs
Shipping informations Package Height: 390 mm	1 / 15.35 inches
Package Width: 330 mm	/ 12.99 inches
Package Depth: 180 mm	/ 7.09 inches
Package Weight: 3.1 kg / 6	•



PART NUMBER

· 13133037

HD 3216T

EAN 8024530001209



DRAWINGS



