

MMS 3404D

DELEGATE MICROPHONE SET

DESCRIPTION

The desktop delegate microphone set MMS 3404D features a latched button to enable the microphone in mixed mode with other active MMS 3404D and MMS 3405P (if no priority button has been pressed on chairman's set). The button is completed with a LED indicator, lit when pressed. Furthermore the microphone capsule has a LED ring that is ON when the microphone is active. The 46 cm gooseneck microphone mounted on the console has a cardioid pattern, while the miniature high quality transducer assures a good sound reinforcement in small size rooms without needing an additional sound reinforcement system. MMS 3404D are cascaded directly to one or both inputs available on MMS 3405P, by means of CAT 5FTP cable provided.



FEATURES

- High quality cardioid microphone
- 46 cm gooseneck length
- Active microphone LEDs ring
- · Push-to-lock button for mic mixed mode
- 1 W built in loudspeaker for sound reinforcement
- Connection to MMS 3405P through CAT5 FTP cable
- Robust shielded enclosure suitable for desktop or semi-flush mounting

Rev. E Last update: 09/11/2022



TECHNICAL SPECIFICATIONS

Microphone specifications	Type:	Electret
	Directivity:	Hypercardioid
	Sensitivity:	65 dB
	Frequency Response (-3dB):	70 Hz ÷ 18 kHz
Console specifications	Console Type:	Conference
	Working with	FORUM 3000
	LED indicators:	Yes
Connections	Connectors:	RJ45
	Cable:	FTP CAT 5
	Max number in daisy-chain:	79
	Mixing:	Yes
Standard compliance	Safety agency:	CE compliant
Physical specifications	Color:	Grey
Size	Height:	63 mm / 2.48 inches
	Width:	170 mm / 6.69 inches
	Depth:	154 mm / 6.06 inches
	Weight:	1 kg / 2.2 lbs
Shipping information	Package Height:	150 mm / 5.91 inches
	Package Width:	520 mm / 20.47 inches
	Package Depth:	190 mm / 7.48 inches
	Package Weight:	1.57 kg / 3.46 lbs

PART NUMBER

· 14322020

MMS 3404D

EAN 8024530010218



DRAWINGS



